

**ASCO UL1008 Withstand and Closing Ratings ^{1,2,7}
(RMS Symmetrical Amps)**

Frame	Switch Rating (Amps)		300, 4000 & 7000 Series				4000 & 7000 Series				7000 Series										
			Current Limiting Fuses				Specific Breaker			Time Based				Short Time Ratings ³ (sec)							
	Transfer Switches	Bypass Switches	480V Max.	600V Max.	Max Size, A	Class	240V Max.	480V Max.	600V Max.	Time (sec)	240V Max.	480V Max.	600V Max.	480V Max.		600V Max.					
														.13	.2	.3	.5	.1	.13	.3	.5
D	30	-	100kA	-	300	J	22kA	22kA	10kA	0.025	10kA	10kA	10kA	-				-			
			200kA	35kA	200	J															
			35kA	35kA	200	RK1															
D	70, 100	-	35kA	35kA	200	RK1	42kA	25kA	10kA	0.025	10kA	10kA	10kA	-				-			
			200kA	35kA	200	J															
D	150	-	35kA	35kA	200	RK1	65kA	25kA	10kA	0.025	10kA	10kA	10kA	-				-			
			200kA	35kA	200	J															
D	200	-	200kA	-	200	J	65kA	25kA	-	0.025	10kA	10kA	-	-				-			
D	230	-	100kA	-	300	J	65kA	25kA	-	0.025	10kA	10kA	-	-				-			
E	260, 400	-	200kA	-	600	J	65kA	42kA	35kA	0.05	35kA	35kA	22kA	-				-			
J	150, 200, 260, 400	150, 200, 230, 260, 400	200kA	200kA	600	J	65kA	50kA	42kA	0.05	65kA	42kA ⁵	35kA	7.5kA	-		-				
					800	L															
J	600	600	200kA	200kA	800	L	65kA	50kA	42kA	0.05	65kA	42kA ⁵	35kA	7.5kA ⁹	-		-				
			200kA	200kA	600	J															
H ⁸	600	600	200kA	200kA	1600	L	65kA	65kA	65kA	0.05	50kA	50kA	50kA	36kA		-		36kA		-	
P ⁸	600	600	200kA	200kA	1600	L	65kA	65kA	65kA	0.05	50kA	50kA	50kA	36kA		30kA		36kA		-	
P ⁸	800	800 - 1200	200kA	200kA	1600	L	65kA	65kA	65kA	0.05	50kA	50kA	50kA	36kA		30kA		36kA		-	
H	800 - 1200	800 - 1200	200kA	200kA	1600 ⁴	L	65kA	65kA	65kA	0.05	50kA	50kA	50kA	36kA		-		36kA		-	
Q ⁸	600-1600	600-1600	200kA	200kA	2000	L	65kA	65kA	65kA	0.05	65kA	65kA	65kA	50kA				50kA			
S ⁸	800 - 1200	800 - 1200	200kA	200kA	2500	L	100kA	100kA	65kA	0.05	100kA	100kA	65kA	65kA				65kA			
G ⁸	1000 - 1200	1000 - 1200	200kA	200kA	2000	L	85kA	85kA	85kA	0.05	85kA	85kA	85kA	-				-			
G	1600 - 2000 (Front Connected TS Only)		200kA	200kA	2500	L	85kA	85kA	85kA	0.05	85kA	85kA	85kA	42kA		36kA		-			
G ⁸	1600 - 2000	1600 - 2000	200kA	200kA	3000	L	125kA ⁶	125kA ⁶	100kA	0.05	100kA	100kA	100kA	42kA		36kA		42kA		-	
S ⁸	1600 - 2000	1600 - 2000	200kA	200kA	2500	L	100kA	100kA	85kA	0.05	100kA	100kA	85kA	85kA		65kA		85kA		65kA	
G	2600 - 3000	2600 - 3000	200kA	200kA	4000	L	100kA	100kA	100kA	0.05	100kA	100kA	100kA	42kA		36kA		42kA		-	
G ⁸	3200	-	200kA	-	4000	L	100kA	100kA	-	0.05	100kA	100kA	-	-				-			
G	4000	4000	200kA	200kA	5000	L	100kA	100kA	100kA	0.05	100kA	100kA	100kA	85kA	65kA		65kA				
U ⁸	2600 - 4000	2600 - 4000	200kA	200kA	5000	L	125kA	125kA	125kA	0.05	125kA	125kA	125kA	100kA				100kA			

- Notes:
- 1) All WCR values indicated are tested in accordance with the requirements of UL 1008, 7th Edition. See ASCO Pub. 1128 for more WCR information
 - 2) Application requirements may permit higher WCR for certain switch sizes.
 - 3) Short Time ratings are provided for applications involving circuit breakers that utilize trip delay settings for system selective coordination
 - 4) Max fuse rating is 1200A on front connected H frame switches
 - 5) Switches utilizing overlapping neutral (code "C") have 35kA, 0.050 Sec time based rating at 480V Max
 - 6) Rating shown is for Bypass switches only, Transfer Switch rating is 100kA
 - 7) See ASCO for Service Entrance Switch ratings
 - 8) These frames are only available on the 7000 Series product
 - 9) Short Time Rating applies to 600A Bypass switch only, the 600A Transfer Switch does not have a Short Time Rating